

No.	SIZE	STAR RATING	TYPE	LOAD INDEX SPEED	TRA CODE	PATTERN NO.	DEPTH (MM)	STANDARD RIM
1	12.00R24	★★★	TL	178A5	IND-4	M08S/B07S	41,5	8,5
2	13.00R25	★★★	TT/TL		E-3	LOFN	28	8,5
3	14.00R24(385/95R24)	★★	TT	170E	E-2	B05N	23	10.00W
4	14.00R24(385/95R24)	★★	TT	170E	E-2	BGZN	23	10.00W
5	14.00R24	★★★	TT	170E	E-4	B03S	38	10.00W
6	14.00R24	★★★	TT	170E	E-3	LOFN	28	10.00W
7	14.00R25	★★★	TT/TL	170E	E-3	LOFN	28	10.00-2.0/10.00-1.5
8	14.00R25	★★★	TL	168B	E-4	B03S	38	10.00-1.5
9	14.00R25(385/95R25)	★★★	TL	170E	E-2	B05N	23	10.00-1.5
10	14.00R25(385/95R25)	★★	TL	170E	E-2	BGZN	23	10.00-1.5
11	15.5R25	★★	TL	176A2/160B	L-2/E-2	BWYN	25	12.00-1.3
12	16.00R24	★★	TL	163	L-2/G-2	BLGN	27	10,00
13	16.00R25	★★★	TL	174F	E-4	B02S	28	14.00-1.5
14	16.00R25	★★★	TL	200A5	IND-4	M08S	72,5	11.25-2.0
15	16.00R25(445/95R25)	★★★	TL	174F	E-2	B05N	28	11.25-2.0
16	16.00R25(445/95R25)	★★	TL	174F	E-2	BGZN	28	11.25-2.0
17	16.00R25	★★★	TL	174F	E-2	BWYN	28	14.00-1.5
18	17.5R25	★★	TL	182A2/167B	L-3/E-3	B01N	28	14.00-1.5
19	17.5R25	★★	TL	182A2/167B	L-3/E-3	BXDN	28	14.00-1.5
20	17.5R25	★★	TL	182A2	L-5	MWS+	68	14.00-1.5
21	17.5R25	★★★	TL	182A2	L-5	MWS+	68	14.00-1.5
22	17.5R25	★★	TL	182A2/167B	L-2/E-2	BWYN	28	14.00-1.5
23	17.5R25	★★	TL	182A2	L-5S	SMS+	65	14.00-1.5
24	17.5R25(445/80R25)	★★★	TL	170E	E-2	B05N	28	14.00-1.5
25	18.00R25	★★	TL	185B	E-4	B06S	47	13.00-2.5
26	18.00R25	★★	TL	204A2	L-5	SMS+	80	13.00-2.5
27	18.00R25	★★★	TL	214A5	IND-4	M08S	63	13.00-2.5
28	18.00R25	★★★	TL	214A5	IND-4	B07S	63	13.00-2.5
29	18.00R25	★★	TL	185B	E-4	B03S	47	13.00-2.5
30	18.00R25(505/95R25)	★★★	TL	186E	E-2	B05N	28	13.00-2.5
31	18.00R33	★★	TL	191B	E-4	B04S	54	13.00-2.5
32	18.00R33	★★	TL	191B	E-4	B06S	49	13.00-2.5
33	18.00R33	★★	TL	191B	E-4	BDRS	54	13.00-2.5
34	18.00R33	★★★	TL	219A5	IND-4	M08S/B07S	73	13.00-2.5
35	20.5R25	★★	TL	193A2/177B	L-3/E-3	B01N	31	17.00-2.0
36	20.5R25	★★	TL	193A2/177B	L-3/E-3	BXDN	31	17.00-2.0
37	20.5R25	★★	TL	193A2	L-5	MWS+	78	17.00-2.0
38	20.5R25	★★	TL	193A2/161B	L-2/E-2	BWYN	31	17.00-2.0
39	20.5R25	★★	TL	193A2	L-5	LCHS+	72	17.00-2.0
40	20.5R25	★★	TL	193A2	L-5S	SMS+	72	17.00-2.0
41	20.5R25(525/80R25)	★★★	TL	179E	E-2	B05N	31	17.00-2.0
42	21.00R33	★★	TL	200B	E-4	B06S	54	15.00-3.0
43	21.00R35	★★	TL	201B	E-4	B04S/BDRS	61	15.00-3.0
44	23.5R25	★★	TL	201A2/185B	L-3/E-3	B01N	34	19.50-2.5
45	23.5R25	★★	TL	201A2/185B	L-3/E-3	B02N	34	19.50-2.5
46	23.5R25	★★	TL	201A2/185B	L-3/E-3	BXDN	42,5	19.50-2.5
47	23.5R25	★★	TL	185B	E-4	BDTS	48	19.50-2.5
48	23.5R25	★★	TL	201A2	L-4	MWS	51	19.50-2.5
49	23.5R25	★★	TL	201A2	L-5	MWS+	87	19.50-2.5
50	23.5R25	★★	TL	201A2/170B	L-2/E-2	BWYN	34	19.50-2.5
51	23.5R25	★★	TL	201A2	L-4	LCHS		19.50-2.5
52	23.5R25	★★	TL	201A2	L-5	LCHS+	78	19.50-2.5
53	23.5R25	★★	TL	201A2	L-5S	SMS+	83	19.50-2.5
54	24.00R35	★★	TL	209B	E-4	B04S	68	17.00-3.5
55	24.00R35	★★	TL	209B	E-4	BDRS	58	17.00-3.5
56	26.5R25	★★	TL	209A2/193B	L-3/E-3	B01N	37	22.00-3.0
57	26.5R25	★★	TL	209A2/193B	L-3/E-3	B02N	37	22.00-3.0
58	26.5R25	★★	TL	209A2/193B	L-3/E-3	BXDN	45	22.00-3.0
59	26.5R25	★★	TL	193B	E-4	BDTS	52	22.00-3.0
60	26.5R25	★★	TL	209A2	L-4	MWS	60	22.00-3.0
61	26.5R25	★★	TL	209A2	L-5	MWS+	96	22.00-3.0
62	26.5R25	★★	TL	209A2/193B	L-2/E-2	BWYN	37	22.00-3.0
63	26.5R25	★★	TL	209A2	L-5	LCHS+	87	22.00-3.0
64	26.5R25	★★	TL	209A2	L-4	LCHS	57	22.00-3.0
65	26.5R25	★★	TL	209A2	L-5S	SMS+	90	22.00-3.0
66	29.5R25	★★	TL	216A2/200B	L-3/E-3	B02N	43,5	25.00-3.5
67	29.5R25	★★	TL	216A2/200B	L-3/E-3	BXDN	48	25.00-3.5

68	29.5R25	★★	TL	200B	E-4	BDTS	57	25.00-3.5
69	29.5R25	★★	TL	216A2	L-4	MWS	75	25.00-3.5
70	29.5R25	★★	TL	216A2	L-5	MWS+	104	25.00-3.5
71	29.5R25	★★	TL	216A2/200B	L-2/E-2	BWYN	43,5	25.00-3.5
72	29.5R25	★★	TL	216A2	E-4	LCHS	57	25.00-3.5
73	29.5R25	★★	TL	216A2	L-5	LCHS+	95	25.00-3.5
74	29.5R25	★★	TL	216A2	L-5S	SMS+	100	25.00-3.5
75	29.5R29	★★	TL	218A2/202B	L-3/E-3	B02N	43,5	25.00-3.5
76	29.5R29	★★	TL	202B	E-4	BDTS	57	25.00-3.5
77	29.5R29	★★	TL	218A2	L-5	MWS+	104	25.00-3.5
78	29.5R29	★★	TL	218A2	L-5	LCHS+	95	25.00-3.5
79	29.5R29	★★	TL	218A2	L-4	LCHS	62,5	25.00-3.5
80	29.5R29	★★	TL	218A2	L-5S	SMS+	100	25.00-3.5
81	35/65R33	★★	TL	224A2	L-5	MWS+	97	28.00-3.5
82	35/65R33	★★	TL	224A2	L-5	LCHS+	97	28.00-3.5
83	35/65R33	★★	TL	224A2	L-4	LCHS	62,5	28.00-3.5
84	35/65R33	★★	TL	224A2	L-5S	SMS+	97	28.00-3.5
85	600/65R25	★★	TL	187A2/178B	L-3/E-3	B02S	35,5	19.5-2.5
86	650/65R25	★★	TL	193A2/180B	L-3/E-3	B02S	38,5	19.50-2.5
87	750/65R25	★★	TL	202A2/190B	L-3/E-3	B02S	44,5	24.00-3.0
88	850/65R25	★	TL	207A2	L-3	B02S	52,5	25.00-3.5
89	875/65R29	★★	TL	214A2/203B	L-3/E-3	B02S	52,5	27.00-3.0
90	2700R49	★★	TL	223B	E-4	HLG01/02	68	19.5-4.0
91	3000R51	★★	TL	230B	E-4	HLG01/02	74	22.00-4.5
92	3300R51	★★	TL	235B	E-4	HLG01/02	80	24.00-5.0
93	3600R51	★★	TL	241B	E-4	HLG01/02	88	26.00-6.0
94	23.5-25-18PR	ANNAITE	TT & TL		L-3/E-3	G-1/G-2	32	19.5/2.5
95	23.5-25-20PR	ANNAITE	TT & TL		L-3/E-3	G-1/G-2	32	19.5/2.5
96	17.5-25-12PR	ANNAITE	TT & TL		L-3/E-3	G-1	26	14.00/1.5
97	17.5-25-16PR	ANNAITE	TT & TL		L-3/E-3	G-1	26	14.00/1.5



B01N      B02N      B02S      B03S      B04S      B05N      B06S



B07S      M08S      MWS/MWS+      SMS+      BDRS      BDTS      BGZN



BLGN      BWYN      BXDN      LOFN      LCHS      HLG02      G-1      G-2